Applicant: DOMESLE

Appl. Ser. No.: 10/535,589

Filing Date: November 30, 2005

Response to Office Action

Page 2 of 6

Please amend the above-identified application as follows:

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (previously presented): Process for the coating of a catalyst support with a catalytically

active coat using a coating dispersion, the catalyst support containing at least two partial

structures which differ in their absorptivity for the coating dispersion, where the absorptivity of

at least one partial structure is modified by precoating of the catalyst support and the catalytic

coat is then applied, wherein the catalyst support is a filter catalyst support, which has a porous

filter mat as a first partial structure and a non-porous metal foil as a second partial structure.

2. (previously presented): Process according to Claim 1, where the precoating is effected

with a material which can be burnt out, evaporated, vaporized or a combination thereof.

3. (original): Process according to Claim 2, where polyvinyl alcohol, wax or a wax

emulsion is used as the material which can be burnt out.

4. (original): Process according to Claim 2, where the precoating is effected with water.

5. (original): Process according to Claim 2, where the precoating is effected with a water-

miscible liquid.

6. (original): Process according to Claim 5, where alcohols are used as the water-miscible

liquid.

7. (original): Process according to Claim 2, where the precoating is effected with a water-

immiscible organic liquid.

Applicant: DOMESLE Appl. Ser. No.: 10/535,589 Filing Date: November 30, 2005 Response to Office Action

Page 3 of 6

8. (original): Process according to Claim 7, where hydrocarbons are used as the water-immiscible organic liquid.

- 9. (previously presented): Process according to Claim 1, where the precoating medium comprises catalytically active material and/or a precursor thereof.
- 10. (cancelled)
- 11. (previously presented): Process according to Claim 1, where the precoating is effected by immersion of the catalyst support in a precoating medium or by absorption of a precoating medium into the catalyst support.
- 12. (previously presented): Process according to Claim 1, where the catalytic coat is dried and/or calcined after application.
- 13. (previously presented): Catalyst which can be produced by a process according to Claim

1.

- 14. (cancelled)
- 15. (cancelled)
- 16. (cancelled)